

ESPAÑOL: PÁGINA 15
FRANÇAISE : PAGE 29

Instruction manual

Belt Sanders



MODEL 503
3" x 24" Belt



MODEL 504
3" x 24" Belt

To learn more about Porter-Cable
visit our website at:

<http://www.porter-cable.com>

PORTER-CABLE
PROFESSIONAL POWER TOOLS

Copyright © 2002 Porter-Cable Corporation

IMPORTANT

Please make certain that the person who is to use this equipment carefully reads and understands these instructions before starting operations.


The Model and Serial No. plate is located on the main housing of the tool. Record these numbers in the spaces below and retain for future reference.

Model No. _____

Type _____

Serial No. _____


Part No. 899602 - 04-26-02

 **WARNING: SOME DUST CREATED BY POWER SANDING, SAWING, GRINDING, DRILLING, AND OTHER CONSTRUCTION ACTIVITIES** contains chemicals known to cause cancer, birth defects or other reproductive harm. Some examples of these chemicals are:

- lead from lead-based paints,
- crystalline silica from bricks and cement and other masonry products, and
- arsenic and chromium from chemically-treated lumber.

Your risk from these exposures varies, depending on how often you do this type of work. To reduce your exposure to these chemicals: work in a well ventilated area, and work with approved safety equipment, such as those dust masks that are specially designed to filter out microscopic particles.

GENERAL SAFETY RULES

 **WARNING: READ AND UNDERSTAND ALL INSTRUCTIONS.** Failure to follow all instructions listed below, may result in electric shock, fire and/or serious personal injury.

SAVE THESE INSTRUCTIONS.

WORK AREA

1. **Keep your work area clean and well lit.** Cluttered benches and dark areas invite accidents.
2. **Do not operate power tools in explosive atmospheres, such as in the presence of flammable liquids, gases, or dust.** Power tools create sparks which may ignite the dust or fumes.
3. **Keep bystanders, children, and visitors away while operating a power tool.** Distractions can cause you to lose control.

ELECTRICAL SAFETY

1. **Grounded tools must be plugged into an outlet properly installed and grounded in accordance with all codes and ordinances. Never remove the grounding prong or modify the plug in any way. Do not use any adapter plugs. Check with a qualified electrician if you are in doubt as to whether the outlet is properly grounded.** If the tools should electrically malfunction or break down, grounding provides a low resistance path to carry electricity away from the user.
2. **Avoid body contact with grounded surfaces such as pipes, radiators, ranges and refrigerators.** There is an increased risk of electric shock if your body is grounded.
3. **Don't expose power tools to rain or wet conditions.** Water entering a power tool will increase the risk of electric shock.
4. **Do not abuse the cord. Never use the cord to carry the tools or pull the plug from an outlet. Keep cord away from heat, oil, sharp edges or moving parts. Replace damaged cords immediately.** Damaged cords increase the risk of electric shock.
5. **When operating a power tool outside, use an outdoor extension cord marked "W-A" or "W".** These cords are rated for outdoor use and reduce the risk of electric shock.

PERSONAL SAFETY

1. **Stay alert, watch what you are doing, and use common sense when operating a power tool. Do not use tool while tired or under the influence of drugs, alcohol, or medication.** A moment of inattention while operating power tools may result in serious personal injury.
2. **Dress properly. Do not wear loose clothing or jewelry. Contain long**

hair. Keep your hair, clothing, and gloves away from moving parts. Loose clothes, jewelry, or long hair can be caught in moving parts.

3. Avoid accidental starting. Be sure switch is OFF before plugging in. Carrying tools with your finger on the switch or plugging in tools that have the switch ON invites accidents.

4. Remove adjusting keys or wrenches before turning the tool ON. A wrench or a key that is left attached to a rotating part of the tool may result in personal injury.

5. Do not overreach. Keep proper footing and balance at all times. Proper footing and balance enables better control of the tool in unexpected situations.

6. Use safety equipment. Always wear eye protection. Dust mask, non-skid safety shoes, hard hat, or hearing protection must be used for appropriate conditions.

TOOLS USE AND CARE

1. Use clamps or other practical way to secure and support the workpiece to a stable platform. Holding the work by hand or against your body is unstable and may lead to loss of control.

2. Do not force tool. Use the correct tool for your application. The correct tool will do the job better and safer at the rate for which it is designed.

3. Do not use tool if switch does not turn it ON or OFF. Any tool that cannot be controlled with the switch is dangerous and must be repaired.

4. Disconnect the plug from the power source before making any adjustments, changing accessories, or storing the tool. Such preventive safety measures reduce the risk of starting the tool accidentally.

5. Store idle tools out of reach of children and other untrained persons. Tools are dangerous in the hands of untrained users.

6. Maintain tools with care. Keep cutting tools sharp and clean. Properly maintained tools, with sharp cutting edges are less likely to bind and are easier to control.

7. Check for misalignment or binding of moving parts, breakage of parts, and any other condition that may affect the tool's operation. If damaged, have the tool serviced before using. Many accidents are caused by poorly maintained tools.

8. Use only accessories that are recommended by the manufacturer for your model. Accessories that may be suitable for one tool may become hazardous when used on another tool.


SERVICE

1. Tool service must be performed only by qualified repair personnel. Service or maintenance performed by unqualified personnel could result in a risk of injury.









2. When servicing a tool, use only identical replacement parts. Follow instructions in the Maintenance Section of this manual. Use of unauthorized parts or failure to follow Maintenance Instructions may create a risk of electric shock or injury.

SPECIFIC SAFETY RULES AND SYMBOLS

1. Hold tool by insulated gripping surfaces when performing an operation where the cutting tools may contact hidden wiring or its own cord. Contact with a "live" wire will make exposed metal parts of the tool "live" and shock the operator.

2. Use proper safety equipment. Wear safety goggles to protect your eyes, wear hearing protection to protect your ears, and wear a protective mask to minimize breathing in the fine dust created while sanding.
3. Sanding of lead-based paint is not recommended. **Lead-based paint should only be removed by a professional.**
4. Always maintain a firm grip on the belt sander handles with both hands to prevent loss of control.
5. Do not operate belt sander without all guards and covers securely in place.
6. Some wood contains preservatives which can be toxic. Take extra care to prevent inhalation and skin contact when working with these materials. Request, and follow, any safety information available from your material supplier.
7.  **WARNING:** There are certain applications for which this tool was designed. Porter-Cable strongly recommends that this tool NOT be modified and/or used for any application other than for which it was designed. If you have any questions relative to its application DO NOT use the tool until you have written Porter-Cable and we have advised you.

Technical Service Manager
Porter-Cable Corporation
4825 Highway 45 North
Jackson, TN 38305

SYMBOL	DEFINITION
V	volts
A	amperes
Hz	hertz
W	watts
kW	kilowatts
μ F	microfarads
l	liters
kg	kilograms
N/cm ²	newtons per square centimeter
Pa	pascals
h	hours
min	minutes
s	seconds
	alternating current
3 	three-phase alternating current
3N 	three-phase alternating current with neutral
	direct current
n_0	no load
	alternating or direct current
	Class II Construction
	splash-proof construction
	watertight construction

.../min revolutions or reciprocation per minute



ADDITIONAL SAFETY RULES FOR PAINT REMOVAL

WARNING: Extreme care should be taken when removing paint. The peelings, residue, and vapors of paint may contain lead, which is poisonous. Exposure to even low levels of lead can cause irreversible brain and nervous system damage; young and unborn children are particularly vulnerable.

Before beginning any paint removal process you should determine whether the paint you are removing contains lead. This can be done by your local health department or by a professional who uses a paint analyzer to check for lead.

LEAD-BASED PAINT SHOULD ONLY BE REMOVED BY A PROFESSIONAL.

Persons removing paint should follow these guidelines:

- 1. KEEP THE WORK AREA WELL VENTILATED.** Open the windows and put an exhaust fan in one of them. Be sure the fan is moving air from inside to outside.
- 2. REMOVE OR COVER** any carpets, rugs, furniture, clothing, cooking utensils and air ducts.
- 3. PLACE DROP CLOTHS** in the work area to catch any paint chips or peelings. Wear protective clothing such as extra work shirts, overalls and hats.
- 4. WORK IN ONE ROOM AT A TIME.** Furnishings should be removed or placed in the center of the room and covered. Work areas should be sealed off from the rest of the dwelling by sealing doorways with drop cloths.
- 5. CHILDREN, PREGNANT OR POTENTIALLY PREGNANT** women and nursing mothers should not be present in the work area until the work is done and all cleanup is complete.
- 6. WEAR A DUST RESPIRATOR** or a dual filter (dust and fume) respirator mask which has been approved by the Occupational Safety and Health Administration (OSHA), the National Institute of Safety and Health (NIOSH), or the United States Bureau of Mines. These masks and replaceable filters are readily available at major hardware stores. Be sure the mask fits. Beards and facial hair may keep the masks from sealing properly. Change filters often. **DISPOSABLE PAPER MASKS ARE NOT ADEQUATE.**
- 7. KEEP FOOD AND DRINK** out of the work area. Wash hands, arms, and face and rinse mouth before eating or drinking. Do not smoke or chew gum or tobacco in the work area.
- 8. CLEAN UP ALL REMOVED PAINT** and dust by wet mopping the floors. Use a wet cloth to clean all walls, sills and any other surfaces where paint or dust is clinging. **DO NOT SWEEP, DRY DUST OR VACUUM.** Use a high phosphate detergent or trisodium (TSP) to wash and mop areas.
- 9. AT THE END OF EACH WORK SESSION** put the paint chips and debris in a double plastic bag, close it with tape or twist ties and dispose of properly.
- 10. REMOVE PROTECTIVE CLOTHING** and work shoes in the work area to avoid carrying dust into the rest of the dwelling. Wash work clothes separately. Wipe shoes off with a wet rag that is then washed with the work clothes. Wash hair and body thoroughly with soap and water.

REPLACEMENT PARTS

When servicing use only identical replacement parts.

MOTOR

Many Porter-Cable tools will operate on either D.C., or single phase 25 to 60 cycle A.C. current and voltage within plus or minus 5 percent of that shown on the specification plate on the tool. Several models, however, are designed for A.C. current only. Refer to the specification plate on your tool for proper voltage and current rating.

CAUTION: Do not operate your tool on a current on which the voltage is not within correct limits. Do not operate tools rated A.C. only on D.C. current. To do so may seriously damage the tool.

EXTENSION CORD SELECTION

If an extension cord is used, make sure the conductor size is large enough to prevent excessive voltage drop which will cause loss of power and possible motor damage. A table of recommended extension cord sizes will be found in this section. This table is based on limiting line voltage drop to 5 volts (10 volts for 230 volts) at 150% of rated amperes.

If an extension cord is to be used outdoors it must be marked with the suffix

		Length of Cord in Feet								
		115V	25 Ft.	50 Ft.	100 Ft.	150 Ft.	200 Ft.	250 Ft.	300 Ft.	500 Ft.
		230V	50 Ft.	100 Ft.	200 Ft.	300 Ft.	400 Ft.	500 Ft.	600 Ft.	1000 Ft.
Nameplate Ampere Rating	0-2	18	18	18	16	16	14	14	12	12
	2-3	18	18	16	14	14	12	12	10	10
	3-4	18	18	16	14	12	12	10	10	8
	4-5	18	18	14	12	12	10	10	8	8
	5-6	18	16	14	12	10	10	8	8	6
	6-8	18	16	12	10	10	8	6	6	6
	8-10	18	14	12	10	8	8	6	6	4
	10-12	16	14	10	8	8	6	6	4	4
	12-14	16	12	10	8	6	6	6	4	2
	14-16	16	12	10	8	6	6	4	4	2
	16-18	14	12	8	8	6	4	4	2	2
	18-20	14	12	8	6	6	4	4	2	2

W-A or W following the cord type designation. For example – SJTW-A to indicate it is acceptable for outdoor use.

RECOMMENDED EXTENSION CORD SIZES FOR USE WITH PORTABLE ELECTRIC TOOLS

FUNCTIONAL DESCRIPTION

FOREWORD

Porter-Cable Belt Sanders are designed for smoothing rough boards, removing old paint and varnish, fine-surfacing wood, metal, plastics, and other materials.

SELECTING AN ABRASIVE BELT

The principal abrasive material used on belts for machine sanding are aluminum oxide and silicon carbide. Aluminum oxide is not as hard as the

silicon carbide, but is tougher and more suited for woods and soft (nonferrous) metals. Silicon carbide is extremely hard and is best suited for surfacing stone, marble and glass.

Abrasives are classed as open-coated (grit spaced) or closed-coated (Grit non-spaced). Closed coatings provide hard, fast cutting action for hardwoods and dense metals while the open coatings are more suited to soft materials and painted surfaces.

To obtain the best finish, start with a "COARSE" grade of abrasive and change to "MEDIUM" and "FINE" grades as work progresses.

A wide range of available PORTER-CABLE Sanding Belts is listed in the back of the manual. Keep a full assortment on hand so that the correct belt will always be available.

INSTALLING AND REMOVING THE ABRASIVE BELT

CAUTION: Disconnect tool from power source.

1. Lay sander on its left side and turn the tension relief lever (A) Fig. 1, locking it under the catch on the plate.
2. Remove the old belt.
3. Install new belt so that arrow, printed on inside of belt, is at the top and pointing toward the front of the sander.




Fig. 1

NOTE: Some sanding belts are bi-directional. These bi-directional belts will not have arrows printed on them. They may be installed to run in either direction.

4. Position the belt so that the outer edge is flush with the outer ends of the pulleys.
5. Release tension lever to restore belt tension.

TO START AND STOP BELT SANDERS

CAUTION: Make sure switch is off and power circuit voltage is the same as the voltage shown on the specification plate on the sander. connect machine to power circuit.

1. Squeeze trigger switch (A) Fig. 2, to start motor. Release trigger to stop motor.
2. A lock button (B) Fig. 2 is provided to keep motor running continually without pressing the trigger.




Fig. 2

3. To lock the trigger switch ON, squeeze the trigger as far as it will go, push in lock button and release trigger.
4. To unlock lock button, squeeze trigger and release, freeing the lock button.

TRACKING THE ABRASIVE BELT

NEVER allow abrasive belt to rub on frame of sander. This action will cause excessive wear to both the sander and belt. To prevent damage, track the belt in the following manner:

CAUTION: Make sure trigger switch is OFF before connecting tool to power circuit.

1. Lift machine clear of work and turn motor on.
2. Turn belt aligning screw (A) Fig. 3, in either direction until edge of belt runs flush with outer edges of the pulleys.
3. Turn motor OFF and allow sander to come to a COMPLETE STOP before putting it down.




Fig. 3

ATTACHING AND CARE OF DUST BAG

MODEL 503 ONLY

The dust bag is completely assembled at the factory. To attach to the sander, push the dust bag tube on to the vacuum housing.

For most efficient operation, empty the dust bag when it is less than half filled. Remove the bag. Unzip the rear of bag and shake out the dust. Occasionally, turn the bag inside out and brush the dust accumulations from the inside.

HOW TO USE THE SANDER

Do not use sander in any position other than that shown in Fig. 4. Using the sander in a vertical or upside-down position may cause excessive gear wear because of a lack of lubrication.



Fig. 4

CAUTION: SECURE WORK and maintain a FIRM GRIP on sander. Friction between sanding belt and work will move the work backward and the sander forward.

CAUTION: ALWAYS be sure switch is OFF before connecting sander to power circuit.

1. HOLD sander OFF the work and start motor.

2. LOWER sander to the work, letting the rear part of the belt touch first. Level the machine as it is moved forward.
3. GUIDE the machine over the work in overlapping strokes, allowing the sander to do the work.
4. AVOID applying excessive pressure when sanding. The weight of the machine is usually sufficient for a fast, smooth finish.
5. WORK BACK and FORTH over a wide area to obtain an even surface.
6. DO NOT tilt the machine or sand with the edge of the belt.
7. Do not pause in any one spot during the sanding operation.
8. Lift sander from work before turning OFF motor.
9. ALWAYS be sure motor has completely stopped before putting sander down.

FAST SANDING ON ROUGH WORK

To smooth a rough surface quickly, use a coarse grit abrasive belt. With the belt positioned diagonally across the grain (see Fig. 5), move the sander in the direction of the grain. Overlap the strokes and work the entire surface from both sides of the board (once with the sander angled to the left and once angled to the right). Smooth the surface by guiding the sander back and forth with the grain. Change the belt to a medium grit and follow the same procedure. Finish by thoroughly sanding over the grain lengthwise. Change again to a fine grit and work back and forth with the grain. Always finish by sanding with the grain.



Fig. 5

REMOVING OLD PAINT AND VARNISH

This sander is an excellent tool for removing old paint and varnish from flat surfaces. Two problems are common to such work: (1) loading the abrasive with the material being removed and (2) overheating the paint or varnish by working too long in one place.

Use a spaced grain or open coat abrasive belt and a single stroke action to overcome the loading problem. Lower the sander at the far end of the work and pull back. Raise the machine and do the same in a different location. Overheating can be avoided by using a fairly quick stroke. A piece of felt about 1/4" thick can be inserted under the shoe for fast spot sanding and for working on stubborn areas of paint and varnish.

SPECIAL SANDING PROCEDURES

Ordinarily the sanding stroke is back and forth. Some materials and some types of operations, however, require a different technique. In rough

sanding, use the machine at an angle. In spot sanding, use the machine with only the front pulley touching the surface (especially required in smoothing excess glue from wood joints). Metals, slate, marble, and plastic materials have no grain. Therefore, the sanding on these workpieces may be done in different directions.

DOORS AND MILL WORK

When sanding doors, cabinet frames, sash, storm windows and screens, avoid working into the cross grain where one member meets another. Notice that the right edge of the belt is visible on your sander. Watch it closely. Work carefully along the edge where the rail meets the stile. If the joint is slightly uneven, use a fine grit abrasive and very light sanding pressure, smoothing the joint prior to making the finishing runs.

GOOD SANDING TECHNIQUE

Getting the feel of the sander is important in obtaining smooth results with minimal labor. Experience will teach the operator how to start the stroke with a sweeping motion that will produce the best results. Use long even strokes with little pressure on the machine.

Overlap each stroke and vary the length of movement so that the results will be even over the entire surface. Always lift the sander from the work before starting and stopping the motor. If the machine drops, it will round the edge. Keep the sander flat on the work surface (Fig 6). **Avoid letting the machine drop as it gets to the end of a workpiece.**(Fig. 7). The sander will work well if these suggestions are followed. The



Fig. 6



Fig. 7

machine works very fast and can do a thorough job in a fraction of the time required by hand sanding. Do not rush the job. Give every surface a thorough sanding with each grade of abrasive before changing to finer grits. Always use the abrasive material and grit size recommended for the job.

SANDING METAL

Belt Sanders will sand metal surfaces to obtain a grained satin finish. Special graphite pads are available that replace the steel shoe on the

bottom of the sander. The softness of these pads helps to blend the graining. (See the accessories listed in the back of this manual for catalog numbers of these pads.)

To replace the steel shoe, (1) remove the retaining screws and clamp bar, and (2) attach the graphite pad.

MAINTENANCE

KEEP TOOL CLEAN

Periodically blow out all air passages with dry compressed air. All plastic parts should be cleaned with a soft damp cloth. NEVER use solvents to clean plastic parts. They could possibly dissolve or otherwise damage the material.

CAUTION: Wear safety glasses while using compressed air.

FAILURE TO START

Should your tool fail to start, check to make sure the prongs on the cord plug are making good contact in the outlet. Also, check for blown fuses or open circuit breakers in the line.

DRIVE PULLEY

The rubber-covered drive pulley at the rear of the machine is tapered from the center to either side to make the abrasive belt run in line with the idler pulley at the front of the machine. After considerable use, the crown of the pulley will wear away and the belt will begin to run off the side of the pulley and cut into the guide block or frame. When this happens, have the drive pulley replaced by your Authorized Porter-Cable Service Station. Check the crown each time the abrasive belt is replaced and tracked. After the belt is tracked to the front pulley, watch it for a few seconds to see that it stays in place on the back pulley. Avoid getting oil and grease on the rubber cover.

BELT GUIDE

The belt guide, or traction block, is made of hardened steel, and is located to the left and to the rear of the idler pulley, fastened to the frame. This block protects the frame of the machine. Always readjust the belt so it moves evenly across (without rubbing) the guide block. This block can be turned over for further use when it becomes worn and uneven. Once both sides are worn and uneven, replace the block. Look for the correct part, specified in the parts list for your sander.

LUBRICATION

Although all PORTER-CABLE tools have been thoroughly lubricated with a sufficient amount of high grade lubricant at the time of manufacture, check the oil level in the gear chamber prior to using your tool and periodically thereafter as follows:

MODEL 503 – CHECKING THE OIL IN THE GEAR CHAMBER:

CAUTION: DISCONNECT TOOL FROM POWER SOURCE.

1. Place sander on a level surface.
2. Remove the lower oil plug from the right side of the sander.
3. Ensure that the oil is level with the bottom of this hole.
4. If oil is required, remove upper oil plug and add a small amount of PORTER-CABLE SPECIAL OIL #803442 (S.A.E. 90 Gear Oil).
5. Repeat steps two through five until oil level is correct. Let any surplus oil run out before replacing plugs.

MODEL 504 – CHECKING THE OIL IN THE GEAR CHAMBER:**CAUTION: DISCONNECT TOOL FROM POWER SOURCE.**

1. Place sander on a level surface
2. Remove oil plug from right side of sander.
3. Ensure that oil is level with bottom of hole.
4. If oil is required, remove oil fill plug from rear of housing (near trigger switch) and add a small amount of PORTER-CABLE SPECIAL OIL #803442 (S.A.E. 90 Gear Oil).
5. Repeat steps two through five until oil level is correct. Let any surplus oil run out before replacing plugs.

ALL MODELS

Lubricate chain case every six months, or at least once a month if sander is in constant use, as follows:

CAUTION: DISCONNECT TOOL FROM POWER SOURCE.

1. Lay machine on its right side and remove cover as shown in Fig. 8.
2. Clean and repack chain case, to about one-half its capacity with PORTER-CABLE SPECIAL GREASE #874809. Do not over fill.



Fig. 8

DRIVE CHAIN CARE

Model 504 – When chain becomes loose, check the chain tension spring and replace if necessary.

Model 503 – Replace the chain if the chain strikes the case.

All Models – Replace the chain when the chain links become loose on the pins.

BRUSH INSPECTION AND LUBRICATION

For your continued safety and electrical protection, brush inspection and replacement on this tool should **ONLY** be performed by an **AUTHORIZED PORTER-CABLE SERVICE STATION** or a **PORTER-CABLE/DELTA FACTORY SERVICE CENTER**.

At approximately 100 hours of use, take or send your tool to your nearest authorized Porter-Cable Service Station to be thoroughly cleaned and inspected. Have worn parts replaced and lubricate with fresh lubricant. Have new brushes installed, and test the tool for performance.

Any loss of power before the above maintenance check may indicate the need for immediate servicing of your tool. **DO NOT CONTINUE TO OPERATE TOOL UNDER THIS CONDITION.** If proper operating voltage is present, return your tool to the service station for immediate service.

SERVICE AND REPAIRS

All quality tools will eventually require servicing or replacement of parts due to wear from normal use. These operations, including brush inspection and replacement, should **ONLY** be performed by either an **AUTHORIZED PORTER-CABLE SERVICE STATION** or a **PORTER-CABLE/DELTA FACTORY SERVICE CENTER**. All repairs made by these agencies are fully guaranteed against defective material and workmanship. We cannot guarantee repairs made or attempted by anyone other than these agencies.

Should you have any questions about your tool, feel free to write us at any time. In any communications, please give all information shown on the nameplate of your tool (model number, type, serial number, etc.).

ACCESSORIES



A complete line of accessories is available from your Porter-Cable • Delta Supplier, Porter-Cable • Delta Factory Service Centers, and Porter-Cable Authorized Service Stations. Please visit our Web Site www.porter-cable.com for a catalog or for the name of your nearest supplier.

WARNING: Since accessories other than those offered by Porter-Cable • Delta have not been tested with this product, use of such accessories could be hazardous. For safest operation, only Porter-Cable • Delta recommended accessories should be used with this product.

PORTER-CABLE LIMITED ONE YEAR WARRANTY

Porter-Cable warrants its Professional Power Tools for a period of one year from the date of original purchase. We will repair or replace at our option, any part or parts of the product and accessories covered under this warranty which, after examination, proves to be defective in workmanship or material during the warranty period. For repair or replacement return the complete tool or accessory, transportation prepaid, to your nearest Porter-Cable Service Center or Authorized Service Station. Proof of purchase may be required. This warranty does not apply to repair or replacement required due to misuse, abuse, normal wear and tear or repairs attempted or made by other than our Service Centers or Authorized Service Stations.

ANY IMPLIED WARRANTY, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WILL LAST ONLY FOR ONE (1) YEAR FROM THE DATE OF PURCHASE.

To obtain information on warranty performance please write to: PORTER-CABLE CORPORATION, 4825 Highway 45 North, Jackson, Tennessee 38305; Attention: Product Service. THE FOREGOING OBLIGATION IS PORTER-CABLE'S SOLE LIABILITY UNDER THIS OR ANY IMPLIED WARRANTY AND UNDER NO CIRCUMSTANCES SHALL PORTER-CABLE BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

This warranty gives you specific legal rights and you may also have other legal rights which vary from state to state.

PORTER-CABLE • DELTA SERVICE CENTERS (CENTROS DE SERVICIO DE PORTER-CABLE • DELTA) (CENTRE DE SERVICE PORTER-CABLE • DELTA)

Parts and Repair Service for Porter-Cable • Delta Power Tools are Available at These Locations
(Obtenga Refaccion de Partes o Servicio para su Herramienta en los Sigüientes Centros de Porter-Cable • Delta)
(Locations où vous trouverez les pièces de rechange nécessaires ainsi qu'un service d'entretien)

ARIZONA

Tempe 85282 (Phoenix)
2400 West Southern Avenue
Suite 105
Phone: (602) 437-1200
Fax: (602) 437-2200

CALIFORNIA

Ontario 91761 (Los Angeles)
3949A East Guasti Road
Phone: (909) 390-5555
Fax: (909) 390-5554
San Leandro 94577 (Oakland)
3039 Teagarden Street
Phone: (510) 357-9762
Fax: (510) 357-7939

COLORADO

Arvada 80003 (Denver)
8175 Sheridan Boulevard, Unit S
Phone: (303) 487-1809
Fax: (303) 487-1868

FLORIDA

Davie 33314 (Miami)
4343 South State Rd. 7 (441)
Unit #107
Phone: (954) 321-6635
Fax: (954) 321-6638
Tampa 33609
4538 W. Kennedy Boulevard
Phone: (813) 877-9585
Fax: (813) 289-7948

GEORGIA

Forest Park 30297 (Atlanta)
5442 Frontage Road, Suite 112
Phone: (404) 608-0006
Fax: (404) 608-1123

ILLINOIS

Addison 60101 (Chicago)
400 South Rohlwing Road
Phone: (630) 424-8805
Fax: (630) 424-8895
Woodridge 60517 (Chicago)
2033 West 75th Street
Phone: (630) 910-9200
Fax: (630) 910-0360

MARYLAND

Elkridge 21075 (Baltimore)
7397-102 Washington Blvd.
Phone: (410) 799-9394
Fax: (410) 799-9398

MASSACHUSETTS

Braintree 02185 (Boston)
719 Granite Street
Phone: (781) 848-9810
Fax: (781) 848-6759
Franklin 02038 (Boston)
Franklin Industrial Park
101E Constitution Blvd.
Phone: (508) 520-8802
Fax: (508) 528-8089

MICHIGAN

Madison Heights 48071 (Detroit)
30475 Stephenson Highway
Phone: (248) 597-5000
Fax: (248) 597-5004

MINNESOTA

Minneapolis 55429
5522 Lakeland Avenue North
Phone: (763) 561-9080
Fax: (763) 561-0653

MISSOURI

North Kansas City 64116
1141 Swift Avenue
P.O. Box 12393
Phone: (816) 221-2070
Fax: (816) 221-2897
St. Louis 63119
7574 Watson Road
Phone: (314) 968-8950
Fax: (314) 968-2790

NEW YORK

Flushing 11365-1595 (N.Y.C.)
175-25 Horace Harding Expwy.
Phone: (718) 225-2040
Fax: (718) 423-9619

NORTH CAROLINA

Charlotte 28270
9129 Monroe Road, Suite 115
Phone: (704) 841-1176
Fax: (704) 708-4625

OHIO

Columbus 43214
4560 Indianola Avenue
Phone: (614) 263-0929
Fax: (614) 263-1238
Cleveland 44125
8001 Sweet Valley Drive Unit #19
Phone: (216) 447-9030
Fax: (216) 447-3097

OREGON

Portland 97230
4916 NE 122 nd Ave.
Phone: (503) 252-0107
Fax: (503) 252-2123

PENNSYLVANIA

Willow Grove 19090
520 North York Road
Phone: (215) 658-1430
Fax: (215) 658-1433

TEXAS

Carrollton 75006 (Dallas)
1300 Interstate 35 N, Suite 112
Phone: (972) 446-2996
Fax: (972) 446-8157
Houston 77055
West 10 Business Center
1008 Wirt Road, Suite 120
Phone: (713) 682-0334
Fax: (713) 682-4867

WASHINGTON

Auburn 98001 (Seattle)
3320 West Valley HWY, North
Building D, Suite 111
Phone: (253) 333-8353
Fax: (253) 333-9613

Authorized Service Stations are located in many large cities. Telephone **800-487-8665** or **731-541-6042** for assistance locating one. Parts and accessories for Porter-Cable • Delta products should be obtained by contacting any Porter-Cable • Delta Distributor, Authorized Service Center, or Porter-Cable • Delta Factory Service Center. If you do not have access to any of these, call **888-848-5175** and you will be directed to the nearest Porter-Cable • Delta Factory Service Center. Las Estaciones de Servicio Autorizadas están ubicadas en muchas grandes ciudades. Llame al **800-487-8665** ó al **731-541-6042** para obtener asistencia a fin de localizar una. Las piezas y los accesorios para los productos Porter-Cable • Delta deben obtenerse poniéndose en contacto con cualquier distribuidor Porter-Cable • Delta, Centro de Servicio Autorizado o Centro de Servicio de Fábrica Porter-Cable • Delta. Si no tiene acceso a ninguna de estas opciones, llame al **888-848-5175** y le dirigirán al Centro de Servicio de Fábrica Porter-Cable • Delta más cercano. Des centres de service agréés sont situés dans beaucoup de grandes villes. Appelez au **800-487-8665** ou au **731-541-6042** pour obtenir de l'aide pour en repérer un. Pour obtenir des pièces et accessoires pour les produits Porter-Cable • Delta, s'adresser à tout distributeur Porter-Cable • Delta, centre de service agréé ou centre de service d'usine Porter-Cable • Delta. Si vous n'avez accès à aucun de ces centres, appeler le **888-848-5175** et on vous dirigera vers le centre de service d'usine Porter-Cable • Delta le plus proche.

CANADIAN PORTER-CABLE • DELTA SERVICE CENTERS

ALBERTA

Bay 6, 2520-23rd St. N.E.
Calgary, Alberta
T2E 8L2
Phone: (403) 735-6166
Fax: (403) 735-6144

BRITISH COLUMBIA

8520 Baxter Place
Burnaby, B.C.
V5A 4T8
Phone: (604) 420-0102
Fax: (604) 420-3522

MANITOBA

1699 Dublin Avenue
Winnipeg, Manitoba
R3H 0H2
Phone: (204) 633-9259
Fax: (204) 632-1976

ONTARIO

505 Southgate Drive
Guelph, Ontario
N1H 6M7
Phone: (519) 836-2840
Fax: (519) 767-4131

QUÉBEC

1515 Ave.
St-Jean Baptiste,
Québec, Québec
G2E 5E2
Phone: (418) 877-7112
Fax: (418) 877-7123

1447, Begin
St-Laurent, (Montréal), Québec
H4R 1V8
Phone: (514) 336-8772
Fax: (514) 336-3505

The following are trademarks of PORTER-CABLE • DELTA (Las siguientes son marcas registradas de PORTER-CABLE • DELTA S.A.) (Les marques suivantes sont des marques de fabricant de la PORTER-CABLE • DELTA): BAMMER®, LASERLOC®, OMNIJIG®, POCKET CUTTER®, PORTA-BAND®, PORTA-PLANE®, PORTER-CABLE®, QUICKSAND®, SANDTRAP®, SAW BOSS®, SPEED-BLOC®, SPEEDMATIC®, SPEEDTRONIC®, STAIR-EASE®, THE PROFESSIONAL EDGE®, THE PROFESSIONAL SELECT®, TIGER CUB®, TIGER SAW®, TORO-BUSTER®, VERSA-PLANE®, WHISPER SERIES®, DURATRONIC™, FRAME SAW™, INNOVATION THAT WORKS™, JETSTREAM™, MICRO-SET™, MORTEN™, NETWORK™, RIPTIDE™, TRU-MATCH™, WOODWORKER'S CHOICE™, THE AMERICAN WOOD SHOP™ (design), AUTO-SET™, B.O.S.S.™, BUILDER'S SAW™, CONTRACTOR'S SAW™, DELTA™, DELTACRAFT™, HOMECRAFT™, JET-LOCK™, KICKSTAND™, THE LUMBER COMPANY™ (design), MICRO-SET™, Q3™, QUICKSET II™, QUICKSET PLUS™, SAFEGUARD II™, SANDING CENTER™, SIDEKICK™, UNIFENCE™, UNIGUARD™, UNIRIP™, UNISAW™, VERSA-FEEDER™, THIN-LINET™, TFS™, Etc.™.

Trademarks noted with ™ and ® are registered in the United States Patent and Trademark Office and may also be registered in other countries. Las Marcas Registradas con el signo de ™ y ® son registradas por la Oficina de Registros y Patentes de los Estados Unidos y también pueden estar registradas en otros países. Marques déposées, indiquées par la lettre ™ et ®, sont déposées au Bureau des brevets d'invention et marques déposées aux Etats-Unis et pourraient être déposées aux autres pays.

Printed in U.S.A.